



Thank you for purchasing the Fanger.

The Fanger is the start of the Coyled Cobra Signature Series line of products brought to you by Lok Grips and is a universal hanger system designed by the Coyled Cobra, a USPSA Grand Master.

Reinforced in the stress areas around the screws and skeletonized to shave weight in the main body area, the Fanger has been designed to look like a Cobra providing both a unique form with superior functionality. It's made of G10, which is lighter than aluminum and steel, making it one of the lightest hanger systems out there. Its universal design makes it compatible with major brands like Bladetech, Safariland, BOSS, Ghost and other holster systems with no modifications necessary when used with the correct hardware. The Cobra design of the Fanger has no corners to rub on your body as you're drawing or moving around providing extra comfort. It has an additional "Smiley" to allow lower positioning of your holsters when mounted to the Fanger. The belt plate securely fastens the Fanger to your competition belt better than other brands.

Additional accessories will be coming out soon adding to the Coyled Cobra Signature Series line of products.

“Train hard so when the time comes, you can strike like a Coyled Cobra”

Warnings:

- This product is only intended for use in competitions by qualified individuals.
- Do not use if you have any questions or concerns about the safe and proper use of this product.
- Do not use if the firearm is not held securely, safely or if any screws are loose.
- No liability is expressed or implied for damage, injury or death which may result from use of this product.
- You are responsible for the safe handling and use of firearms.
- Use of this product may expose user to chemicals known to the state of California to cause cancer or reproductive harm. Do not eat, drink, lick, taste or swallow.

Fanger Instructions

1. Choose belt mounting solution (Fanger Belt Plate, Blade Tech Tek-Lok, Ghost Quick Detach, DAA Lynx) and follow instructions for mounting that solution to the Fanger as instructed below starting on page 2.
2. Attach Ghost swivel joint mount or holster body directly to Fanger using supplied round-head screws included with your Ghost holster. The longer screw with hip spacer included with your Ghost holster should be installed in the center cutout and the shorter screw in the corresponding curved slot. If the height is desired to be lower, then use both curved slots and adjust accordingly. Be careful not to overtighten as that may result in stripping the threading in the holster.

If more space is desired between Fanger and holster body, a spacer kit is available (sold separately) to add ½ inch.

Note: While you can use the 2 screws included with your Ghost hanger to attach the holster or swivel joint, the screw length is shorter than recommended and it is recommended to purchase longer screws for use with the Fanger. Using the shorter screws may not give enough threading to secure the mount to the Fanger and may result in stripping the threads. **The optional spacer kit comes with the correct length screws** as well as give more clearance for your thumb between the belt and holster on the draw.

The optional Spacer Kit is only for use with the Hydra P+ that has the rotating joint mount. The regular Hydra P does not have the rotating joint.

3. Test location of holster with unloaded firearm. If more adjustments are needed for location and position, adjust to preferred height and tilt by changing screw positions on the Fanger and swivel joint/holster and repeating steps 1 and/or 2 if necessary. Verify spacing between gun and belt and the gun height meets rule requirements.
4. It is recommended to apply thread locker to all screws so they don't accidentally come loose.



With Ghost Hydra P+



**With Hydra P+
And Optional Spacer Kit**

Fanger Instructions for use with Fanger Belt Plate

1. Attach 2 screws for the belt plate through the top 2 holes of the belt plate to the Fanger with enough space to insert the belt loosely from the bottom of the belt plate. Hold the belt between the belt plate and Fanger and align the belt cutout and loosely install the remaining 2 bottom screws. Once the Fanger is in the desired location on the belt, tighten all 4 screws in a cross pattern to evenly tighten the screws securely mounting the Fanger with attached holster to the belt. Be careful not to overtighten. Attaching velco (not included) on the back of the belt plate as pictured below will add more velco surface areas when used with the inner competition velco belts.



Fanger Instructions for use with Ghost Holster Quick Detach belt mount

Note: While you can use the 4 screws included with your Ghost hanger and Quick Detach mount, the screw length is shorter than recommended and it is recommended to purchase longer screws for use with the Fanger. Using the shorter screws may not give enough threading to secure the QD mount to the Fanger and may result in stripping the threads.

1. Attach the 4 screws through the Ghost QD mount to the Fanger. Tighten all 4 screws in a cross pattern to evenly tighten the screws securely mounting the Fanger. Be careful not to overtighten.



Fanger Instructions for use with Blade Tech Tek-Lok

1. Attach the 3 screws (sold separately) through the Tek-Lok mount to the Fanger. Tighten all 3 screws evenly to securely mount to the Fanger. Be careful not to overtighten.



Fanger Instructions for use with DAA Lynx Belt

1. Attach the 2 screws included with your Lynx to the top 2 center holes in the Fanger. Tighten both screws evenly to securely mount the Fanger. Be careful not to overtighten.



Additional configurations:

Fanger with Ghost Thunder

